

K60 Series



The K60 gaskets are pierced elastomeric seals. The surface of the seal is molded to form two thicknesses. The piercings of the gasket allows the seal to always be centered. The extra thicknesses of the surface of the seal permits a better resistance to pressure, at equivalent tightening torque, which increases the seal.

Dimensions	D	T	d	D1	n-Øe
½" (15 mm)	89	3	22	61	4-15
¾" (20 mm)	98	3	28	70	4-15
1" (25 mm)	108	3	34	80	4-15
1 ¼" (32 mm)	117	3	44	89	4-15
1 ½" (40 mm)	127	3	50	99	4-15
2" (50 mm)	152	3	61	120	4-19
2 ½" (65 mm)	178	3	74	140	4-19
3" (75 mm)	190	3	90	153	4-19
4" (100 mm)	229	3	116	190	8-19
5" (125 mm)	254	3	142	216	8-22
6" (150 mm)	279	3	170	241	8-22
8" (200 mm)	343	3	220	298	8-22
10" (250 mm)	406	3	275	362	12-25
12" (300 mm)	483	3	326	432	12-25
14" (350 mm)	533	3	359	476	12-29
16" (400 mm)	597	3	409	540	16-29
18" (450 mm)	635	3	459	578	16-32
20" (500 mm)	698	3	510	635	20-32
24" (600 mm)	915	3	612	750	20-35

- Available in EPDM or FPM
- Ideal for thermoplastic piping systems
- Molded flange seal with double O-ring profile
- Better seal than a conventional gasket
- Excellent chemical resistance (FPM)
- Equal surface pressure
- Full Face
- Reusable

Specifications

- ANSI 150
- EPDM : -10 °C to 130 °C
FPM : -5 °C to 150 °C
- Durometer
EPDM : 70 A
FPM : 70 A

